EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	1	"20020010750"	US-PGPUB; USPAT	OR	OFF	2006/11/08 10:15
L2	5047	(standby idle backup) and redundan$2 and (primary master) same (secondary slave) and (@ad<"20000428" @rlad<"20000428")	US-PGPUB; USPAT	OR	ON	2006/11/08 10:17
L3	865	(standby idle backup) and modem and Y and redundan$2 and (primary master) same (secondary slave) and (@ad<"20000428" @rlad<"20000428")	US-PGPUB; USPAT	OR	ON	2006/11/08 10:18
L4	378	(standby idle backup) and modem and (split$4 Y) near3 (connect$3 interfac$3 link bus buffer queu$4 channel port cable) and redundan$2 and (primary master) same (secondary slave) and (@ad<"20000428" @rlad<"20000428")	US-PGPUB; USPAT	OR	ON	2006/11/08 10:20
L5	311	(standby idle backup) and modem and (split$4 Y) near3 (connect$3 interfac$3 link bus buffer queu$4 channel port cable) and redundan$2 and (primary master) same (secondary slave) and (@ad<"20000428" @rlad<"20000428") and configur$5 with (data information attribute parameter)	US-PGPUB; USPAT	OR	ON	2006/11/08 10:21
L6	70	(standby idle backup) and modem and (split$4 Y) near3 (connect$3 interfac$3 link bus buffer queu$4 channel port cable) and redundan$2 and (primary master) same (secondary slave) and (@ad<"20000428" @rlad<"20000428") and configur$5 with (data information attribute parameter) and (interpret$5 conver$4 translat$3 transcod$3 rewrit$4 overwrit$4) near5 messag$3	US-PGPUB; USPAT	OR	ON	2006/11/08 10:22

L7	69	(standby idle backup) and modem and (split$4 Y) near3 (connect$3 interfac$3 link bus buffer queu$4 channel port cable) and redundan$2 and (primary master) same (secondary slave) and (@ad<"20000428" @rlad<"20000428") and configur$5 near3 (data information attribute parameter) and (interpret$5 conver$4 translat$3 transcod$3 rewrit$4 overwrit$4) near5 messag$3	US-PGPUB; USPAT	OR	ON	2006/11/08 10:25
L8	60	(standby idle backup) and (controller transceiver modem) same (split$4 Y) near3 (connect$3 interfac$3 link bus buffer queu$4 channel port cable) and redundan$2 and (primary master) same (secondary slave) and (@ad<"20000428" @rlad<"20000428") and configur$5 near3 (data information attribute parameter) and (interpret$5 conver$4 translat$3 transcod$3 rewrit$4 overwrit$4) near5 messag$3	US-PGPUB; USPAT	OR	ON	2006/11/08 10:24
L9	10801	reset with (routing path algorithm)	US-PGPUB; USPAT	OR	ON	2006/11/08 10:24
L10	38	reset with (routing path algorithm) and 8	US-PGPUB; USPAT	OR	ON	2006/11/08 10:25
L11	47	(standby idle backup failover failsafe) and (split$4 Y) near3 (connect$3 interfac$3 link bus buffer queu$4 channel port cable) and redundan$2 and (primary master) same (secondary slave) and (@ad<"20000428" @rlad<"20000428") and configur$5 near3 (data information attribute parameter) and (interpret$5 conver$4 translat$3 transcod$3 rewrit$4 overwrit$4) near5 messag$3 and 9	US-PGPUB; USPAT	OR	ON	2006/11/08 10:29

L12	48	(standby) and (split$4 Y) and redundan$2 and (primary master) same (secondary slave backup standby) and (@ad<"20000428" @rlad<"20000428") and configur$5 near3 (data information attribute parameter) and (interpret$5 conver$4 translat$3 transcod$3 rewrit$4 overwrit$4) near5 messag$3 and 9	US-PGPUB; USPAT	OR	ON	2006/11/08 10:37
L14	38	(standby) and (split splitter Y) same (interchang$3 exchang$3 interact$3) and redundan$2 and (primary master) same (secondary slave backup standby) and (@ad<"20000428" @rlad<"20000428") and configur$5 near3 (data information attribute parameter) and (interpret$5 conver$4 translat$3 transcod$3 rewrit$4 overwrit$4) near5 messag$3 and 9	US-PGPUB; USPAT	OR	ON	2006/11/08 10:34
L15	45	(standby) and (split$4 concurrent parallel) and redundan$2 and (primary master) same (secondary slave backup standby) and (@ad<"20000428" @rlad<"20000428") and configur$5 near3 (data information attribute parameter) and (interpret$5 conver$4 translat$3 transcod$3 rewrit$4 overwrit$4) near5 messag$3 and 9	US-PGPUB; USPAT	OR	ON	2006/11/08 10:37